

Ceiling Light Series I

5CCT Ultra-thin Flush Mount

Catalog Number: Project Name: Note: Date: Type:



BASED ON SAMPLE SETTING.ACTUAL LUMENS MAY VARY.				
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
5FMCT10SR05WH	5inch	10W	2700K 3000K 3500K 4000K 5000K	525Lm 551Lm 596Lm 650Lm 578Lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
7FMCT15SR05WH	7inch	15W	2700K 3000K 3500K 4000K 5000K	980Lm 1044Lm 1090Lm 1127Lm 1072Lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
9FMCT18SR05WH	9inch	18W	2700K 3000K 3500K 4000K 5000K	1042Lm 1129Lm 1214Lm 1240Lm 1179Lm

TECHNICAL SPECIFICATION		
VOLTAGE	120V	
POWER FREQUENCY	60Hz	
POWER FACTOR	>0.9	
5CCT	2700K 3000K 3500K 4000K 5000K	
CRI	90	
BEAM ANGLE	120°	
MATERIAL	AL+Plastic+PS	
LIFESPAN	≥50,000hours	
OPERATING TEMP	(-4°F~ 113°F) -20~45°C	
DIMMING	Triac Dimming	
RATING	Suitable for Damp Locations	
WARRANTY	5 year limited	











FEATURES

- · Emits evenly, without halo and shadow
- Fit 4" J-Box and 5"/6" Housing
- 2 installation ways supporting: Suface mount and Retrofit
- Color removable trim available (sold separately): Brushed Nickel, Black, Bronze

STYLISH AND SLIM DESIGN

This ultra bright LED Flush Mount is only 0.5 inch thickness.

The smooth surface is suitable for a variety of decorative styles.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed. Energy Star. Title 24.



Ceiling Light Series I 5CCT Ultra-thin Flush Mount

Catalog Number: Project Name: Note: Date: Type:

5inch & 7inch & 9inch Easily flip the switch for desired CCT




Products View



Recommended Dimmer

LUTRON		LEVITON
TG-600PR-WH S-600PR-WH CTCL-153PDH-WI TGCL-153PH-LA SLV-600P-AL DV-600PR-WH	SCL-153PH-WH GT-600P HDVCL-153P PD-6WCL MSCL-0P153M MACL-153M//MA-R	6672 6674 DSL06 RNL06 IPL06

SIZE & DIMENSION





SIZE	А	В	С
7inch	Φ5.51"(140mm) Φ7.48"(190mm) Φ8.86"(225mm)	0.5"(12.75mm)	1"(25.5mm)

REMOVABLE TRIM(SOLD SEPARATELY)









ACCESSORIES

	SURFACE MOUNT ACCESSORIES	
PART	DESCRIPTION	QUANTITY
a d e	Mounting Bracket Wire Nuts Screws 1	1 3 2

R	ETROFIT INSTALLATION ACCESSORI	ES
PART	DESCRIPTION	QUANTITY
a b c d f	Mounting Bracket Springs E26 Adapter Wire Nuts Screws 2	1 2 1 3 2



