

Date: Catalog Number: Project Name: Note: Type:









BACED ON	CAMDI E CETTII	NG.ACTUAL LUMEN	IC MAY VARY
DASED ON	SMINIT LL SLITTI	NO.AGI OAL LUIVILI	IJ MAI VAILL.

MODEL#	SIZE	WATTAGE	CCT	LUMENS
4EJCT09SR-NS	4inch	9W	6500K	630Lm
	2W (Back light)			
MODEL#	SIZE	WATTAGE	CCT	LUMENS
6EJCT13R-NS	6inch	13W	6500K	1100Lm
	3W (Back light)			
MODEL#	SIZE	WATTAGE	CCT	LUMENS
8EJCT18R-NS	8inch	18W	6500K	1400Lm
─			4٧	V (Back light)

TECHNICAL SPECIFICATION				
VOLTAGE	120V			
POWER FREQUENCY	60Hz			
POWER FACTOR	>0.9			
MAIN LIGHT CCT	2700K~ 6500K			
BACK LIGHT CCT	RGB			
CRI	90			
BEAM ANGLE	120°			
MATERIAL	AL+PS			
LIFESPAN	≥50,000hours			
OPERATING TEMP	(-4°F~ 113°F) -20~45°C			
DIMMABLE	Mobile APP Dimmable			
RATING	Suitable for Wet Locations			
WARRANTY	5 year limited			









FEATURES

Download the "Smart Life" or "tuya" APP to connect and enjoy intelligent control. NOTE: Only support 2.4 GHz Wi-Fi.

- 16 million colors availiable.
- Support Bluetooth+WIFI+Voice control.
- · Control the light in groups.
- Timer function, setting lights on/off automatically.
- Multi preset scene modes and DIY scenes to fits any occasions.

INSTALLATION

No existing recessed housing or junction box required. Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-1% dimming to choose the desired brightness.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

FCC.FCC-ID.





Catalog Number: Project Name: Note: Date: Type:







SIZE & DIMENSION & HOLE CUTOUT

