

Commercial Grade Series I

5CCT 3Wattage Commercial Downlight

Catalog Number: Project Name: Note: Date: Type:



BASED ON SAMPLE SETTING.ACTUAL LUMENS MAY VARY

MODEL#	SIZE	WATTAGE	LUMENS
4CMCT12LR05	4inch	6W-9W-12W	628lm-893lm-1159lm
6CMCT22LR05	6inch	12W-17W-22W	1296Lm-1694Lm-2194Lm
8CMCT30LR05	8inch	17W-24W-30W	1871Lm-2621Lm-3273Lm
10CMCT38LR0	5 10inch	22W-30W-38W	2356Lm-3141Lm-3892Lm

FEATURES

- •High luminous efficacy, up to 100LM/W
- •High quality Aluminium shell with frosted PC diffuser
- •Color removable trim available (sold separately): Brushed nickel, Black, Bronze

TECHNICAL SPECIFICATION

L OI LOII IOMITOIT	i Loi ii ii o
120-277V	VOLTAGE
50/60Hz	POWER FREQUENCY
>0.9	POWER FACTOR
2700K 3000K 3500K 4000K 5000K	5CCT
90	CRI
100°	BEAM ANGLE
AL+PC	MATERIAL
≥50,000hours	LIFESPAN
(-4°F~ 113°F) -20~45°C	OPERATING TEMP
0-10V dimming	DIMMABLE
Suitable for Wet Locations	RATING
5 year limited	WARRANTY

INSTALLATION

Easy fit installation, spring-action housing clips. Suitable for most new constructions.

DIMMING

Supports 0-10V dimming from 100% to 10%.

ELECTRICAL

This fixture is built with the highest quality drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.















ETL Listed. Energy Star. FCC. Title 24.




Commercial Grade Series I

5CCT 3Wattage Commercial Downlight

Catalog Number: Project Name: Note: Date: Type:

Selectable wattage

4inch:6W-9W-12W 6inch:12W-17W-22W 8inch:17W-24W-30W 10inch:22W-30W-38W



Selectable CCT


2700K, 3000K, 3500K, 4000K, 5000K





DIMENSION





SIZE	HOLE SIZE	
4inch	4 21/64"(110mm)	
6inch	6 19/64" (160mm)	
8inch	8 5/64"(205mm)	
10inch	8 31/32"(228mm)	

RECOMMENDED DIMMER		
LUTRON	LEGRAND	
RMJS-8T-DV-B Diva DVSTV MS-Z101-WH DVSTV-WH	RH4FBL3PW	

TRIM RING REPLACEMENT (SOLD SEPARATELY)



Brushed nickel







ACCESSORIES



Hole cutout card

Wire nuts