

## DESCRIPTION

5CCT LED Downlight Retrofit Kit uses DOB solution technology. It has a classic, low-profile design which allowing users to have a stylish look with efficient lighting. Can be install into any indoor 4"/5"/6" housing.

Light to 2700K warm white, 3000K soft white, 3500K natural white, 4000K cool white, or 5000K bright white.

With a damp location rating, this unit is ideal for new and old construction, remodels, soffit, eaves, shower etc.

Ideal for bedroom, kitchen, bathroom, living room, garage, basement, patio, porch, closet and more etc.



### BASED ON SAMPLE SETTING. ACTUAL LUMENS MAY VARY.

MODEL#	WATTAGE	5CCT	LUMENS
4HVCT10LRWH	10W	2700K	710Lm
		3000K	798Lm
		3500K	837Lm
		4000K	856Lm
		5000K	813Lm

MODEL#	WATTAGE	5CCT	LUMENS
6HVCT15LR05	15W	2700K	1080Lm
		3000K	1102Lm
		3500K	1114Lm
		4000K	1150Lm
		5000K	1109Lm

## TECHNICAL SPECIFICATION

VOLTAGE	120V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
5CCT	2700K   3000K   3500K   4000K   5000K
CRI	90
BEAM ANGLE	100°
MATERIAL	PC+AL
LIFESPAN	≥50,000hours
OPERATING TEMP	(-4°F~ 113°F) -20~45°C
DIMMABLE	Triac Dimming
RATING	Suitable for Damp Locations
WARRANTY	5 year limited

## FEATURES

- Retrofits in existing incandescent can housing
- E26 screw base adapter connects directly to standard socket
- 90+ CRI, superior color rendering performance
- Baffle/Smooth Trim

## DIMMING

Triac dimmable down to 5%. Compatible with most major brands of dimmers.

## ENERGY SAVINGS

80% more energy savings than halogen lamps.

## INSTALLATION

Easy installation with universal E26 connectors. Fit 4" , 5" and 6" compatible housings.

## LIFESPAN

This luminaire is built with the highest quality 120V drivers, ensuring energy efficiency. With a lifespan of 50,000 hours, it can last decades under normal operation!

## LISTING


ETL Listed. Energy Star. Title24.



Catalog Number :      Project Name :      Note :      Date :      Type :



**SIZE & DIMENSION**



**RECOMMENDED DIMMER**

LUTRON		LEVITON
TG-600PR-WH	SCL-153PH-WH	6672
S-600PR-WH	GT-600P	6674
CTCL-153PDH-WH	DVCL-153P	DSL06
TGCL-153PH-LA	PD-6WCL	RNL06
SLV-600P-AL	MSCL-OP153M	IPL06
DV-600PR-WH	MACL-153M//MA-R	

**ACCESSORIES**



E26 Adapter