

Gimbal Series III

5CCT Round Gimbal Recessed Downlight

Catalog Number: Project Name: Note: Date: Type:

DESCRIPTION With color adjustable and features 180° rotation, 20° tilt, and 120° beam angle to highlight architectural or artistic elements in your home. Suitable for Wet Location. Widely used in narrow ceilings, kichens,bars, living room, bedroom,bathroom, hallway, hotel, office, library and many other places, where you need a bright light.

BASED ON SAMPLE SETTING.ACTUAL LUMENS MAY VARY.					
MODEL#	WATTAGE	5CCT	LUMENS		
		2700K	548Lm		
		3000K	557Lm		
4EJCT10TRWH	10W	3500K	673Lm		
		4000K	682Lm		
		5000K	661Lm		
MODEL#	WATTAGE	5CCT	LUMENS		
		2700K	1001Lm		
		3000K	1015Lm		
6EJCT14TRWH	14W	3500K	1036Lm		
		4000K	1052Lm		
		5000K	1022Lm		

. SPECIFICATION	TECHNICAL
120V	VOLTAGE
60Hz	POWER FREQUENCY
>0.9	POWER FACTOR
2700K 3000K 3500K 4000K 5000K	5CCT
90	CRI
120°	BEAM ANGLE
AL+PC	MATERIAL
≥50,000hours	LIFESPAN
(-4°F~ 113°F) -20~45°C	OPERATING TEMP
Triac Dimming	DIMMING
Suitable for Wet Locations	RATING
5 year limited	WARRANTY

c Ustro





FEATURES

- Adjustable lens, perfectly illuminate your individual space.
- · Canless installation, no housing required.
- Wet location, perfect for showers, bathrooms.

INSTALLATION

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed.



Gimbal Series III

5CCT Round Gimbal Recessed Downlight

Catalog Number: Project Name: Note: Date: Type:

	i	i		
Easily flip the switch for desired CCT	180° Rotation	1	20° Tilt Range	
Lasily hip the switch for desired cor	100 Hotation	1	20 Hit Hallye	







SIZE & DIMENSION & HOLE SIZE

SIZE	DIMENSION	HOLE SIZE
4inch	96.277(136mm) 1.347(34.1mm) 1.347(34.1mm) 1.347(34.1mm)	Φ4 21/64"(110mm)
6inch	(mail 152)-1750 (mail 152)-1751 (mail 152)-175	Ф6 19/64"(160mm)

RECOMMENDED DIMMER

	LUTROI	V		LEVITO	ON
TG-600PR-WH S-600PR-WH CTCL-153PDH-WH	TGCL-153PH-LA SLV-600P-AL DV-600PR-WH	SCL-153PH-WH GT-600P DVCL-153P	MSCL-0P153M MACL-153M//MA-R PD-6WCL	6672 6674 DSL06	RNL06 IPL06

ACCESSORIES







Connector



Hole cutout card