

# **Commercial Grade E Series**

Led Split Deep Regress Commercial Downlight

Catalog Number: Project Name: Note: Date: Type:



- LED split deep regress commercial downlight series are available in 3 different light engine. Each light engine could fitting 6", 8", 10" round trims.
- The innovative separable design of junction box and trim makes it more flexible. One engine allows for seamless integration of multiple trim sizes with easy and tool-free installation.
- Easy-fit installation comes from the adjustable butterfly clips. It is designed for recessed application
- It is suitable for commercial and public places and elegantly decorates the ambience, such as shopping mall, hospital, airport, hotel lobby etc

### **FEATURES**

- Spun aluminum reflector integrate with haze finish and white trim ring with shadow free.
- Durable tension clips, allow for fast and easy flush installation.
- 0-10V dimmable.
- Available in 3 wattages and 5 CCT tunable.

TECHNIC	AI OD	FOILI	ATION
I FI - FINIII -	M		- V I II I IV

12	20-277V
ENCY	50/60Hz
}	>0.9
2700K   3000K   3500K  4000K	K   5000K
	90
	100°
	AL+PC
≥50,0	000hours
MP <b>(-4°F~ 113°F) -2</b>	20~45°C
0-10V di	limmable
Suitable for Wet Lo	ocations.
5 year	ar limited









#### INSTALLATION

Easy assembly, tool-free installation.

#### **ELECTRICAL**

This fixture is built with the highest quality drivers, ensuring energy efficiency.

## **ENERGY SAVINGS**

80% more energy savings than halogen lamps.

#### **LISTING**

ETL Listed.







MODEL	1	TRIM	1	WATTAGE	1	LUMEN
SPCM65DR05	<u> </u>	DT-6R		 	I	3850lm/4700lm/5550lm
	I I	DT-8R	1	45W-55W-65W		4050lm/4950lm/5850lm
		DT-10R	<u> </u>			4300lm/5250lm/6150lm



# **Commercial Grade E Series**

Led Split Deep Regress Commercial Downlight

Catalog Number: Project Name: Note: Date: Type:



Selectable CCT & Selectable Wattage

The innovative separable design of junction box and trim makes it more flexible.

Easy-fit installation comes from the adjustable butterfly clips.







	6" Light Engine		8" Light Engine	е	10" Light E	ngine	Hole Cutout
6" Round Trim	\$07/(2277mm) 335/(85mm) 4.69(1) 9.7mm)	305.(558mm) 3.11.(86.5mm) 1.887(40.250mm)	8 67 (1 52 mm) 3.4 (185 mm) 3.4 (185 mm) 4.4 (195 mm)	1.58 (40.22).2016	8.0°7(06sm) 2.7(177.7mm) 4.69(119.2mm) 3.74(8pm)	9.02'(229mm)) 9.02'(229mm)) 9.11.66.6mm)	Ф6 19/64" (160mm)
8" Round Trim	10.02(25sm) 5.42(1927m) 3.35(95m) 4.69(1192m)	3.07.(573/mu) 3.07.(573/mu) 3.41.786 Smm)	10 057(256mm) 4.65(119.27mm) 3.74(95mm)	9.02(529mm) 3.47 (86.5mm)	1.000(1556mm) 4.667(1)(3.7mm) 3.247(95mm) 4.667(1)(3.7mm)	305,(553am) 305,(553am) 305,(553am)	48 5/64" (205mm)
10" Round Trim	1 ACT (25 mm) 4 497 (15 mm) 5 5 42 (13 7 mm) 5 5 5 (15 mm) 6 5 5 (15 mm) 7 mm) 7 10 mm	3.022(552kmin) 1.587 (40.22mm) 29.17 (98.58mm)	1.42(20)0mm 4.02(1152/mm) 3.74(95mm) 3.74(95mm)	9.02'(229mm) (um27ch) 38' (	1.427260m) 2.267(18.7mm) 3.27(95mm)	0 05,(5750km)) 1 55 (40.250km)	+ Ф8 31/32* (228mm)

# **RECOMMENDED DIMMER**

	LEGRAND			
RMJS-8T-DV-B	Diva DVSTV	MS-Z101-WH	DVSTV-WH	RH4FBL3PW