

Retrofit Kit Series
5CCT Square Retrofit Kit

Catalog Number: Project Name: Note: Date: Type:



BASED ON SAI	MPLE SE	TTING.ACTUAL	LUMENS MA	Y VARY.
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
4HVCT10LSWH	4inch	10W	2700K 3000K 3500K 4000K 5000K	684Lm 693Lm 711Lm 723Lm 705Lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
6HVCT15LSWH	6inch	15W	2700K 3000K 3500K 4000K 5000K	954Lm 973Lm 991Lm 1008Lm 987Lm

TECHNICAL SPECIFICATION		
VOLTAGE	120V	
POWER FREQUENCY	60Hz	
POWER FACTOR	>0.9	
5CCT	2700K 3000K 3500K 4000K 5000K	
CRI	90	
BEAM ANGLE	100°	
MATERIAL	AL+PC	
LIFESPAN	≥50,000hours	
OPERATING TEMP	(-4°F~ 113°F) -20~45°C	
DIMMABLE	Triac Dimming	
RATING	Suitable for Damp Locations	
WARRANTY	5 year limited	









FEATURES

- Perfect for retrofit jobs
- · No tools required for installation
- Emits evenly, without halo or shadows
- Continuous dimming from 100% to 5% with many Triac Dimmers
- Built-in Driver

INSTALLATION

Fit in 4, 6 inch compatible housing cans directly, no additional accessories are required.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-5% dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING


ETL Listed.




Catalog Number: Project Name: Note: Date: Type:





Selectable CCT 2700K,3000K,3500K,4000K,5000K



SIZE & DIMENSION









RECOMMENDED DIMMER

LUTRON	LEVITON	
TG-600PR-WH	SCL-153PH-WH	
S-600PR-WH	GT-600P	6672
CTCL-153PDH-WH	DVCL-153P	6674
TGCL-153PH-LA	MSCL-OP153M	IPL06
SLV-600P-AL	PD-6WCL	DSL06
DV-600PR-WH	MACL-153M//MA-R	RNL06

ACCESSORIES



E26 Adapter