

Catalog Number :

Project Name :

Note :

Date :

Type :

## DESCRIPTION

It features an innovative borderless design, showcasing minimalist aesthetics; offers 5 levels of color temperature adjustment for versatile scene requirements; and is equipped with a rotatable mounting plate for easy ceiling installation, ensuring quick and efficient setup.

It is suitable for office, family, hotels, corridors, shopping centers, schools, books and other places.



**Based on sample setting. Actual lumens may vary.**

MODEL	SIZE	WATTAGE	5CCT	LUMENS
CL03-05-10-LC5-D0	5inch	10W	2700K	750lm
			3000K	785lm
			3500K	800lm
			4000K	830lm
			5000K	850lm
CL03-07-15-LC5-D0	7inch	15W	2700K	1350lm
			3000K	1425lm
			3500K	1470lm
			4000K	1520lm
			5000K	1545lm
CL03-09-18-LC5-D0	9inch	18W	2700K	1460lm
			3000K	1495lm
			3500K	1500lm
			4000K	1512lm
			5000K	1545lm

## Technical Specification

VOLTAGE	120-277V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
5CCT	2700K   3000K   3500K   4000K   5000K
CRI	90
BEAM ANGLE	120°
MATERIAL	AL+PC
FINISH	Black / White
LIFESPAN	≥50,000hours
OPERATING TEMP	(-4°F ~ 113°F) -20~45°C
DIMMING	0-10V Dimmable
RATING	Suitable for Wet Locations
WARRANTY	5 year limited

## Listing

ETL Listed.



## Installation

Support surface mount; Fit 2.75 or 3.5 inch J-Box;

## Electrical

This fixture is built with the highest quality 120-277V drivers, ensuring energy efficiency.

## Dimming

Compatible with most triac dimmers to give user a smooth 100%-0% dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.







## Energy Savings

80% more energy savings than halogen lamps.

Catalog Number: Project Name: Note: Date: Type:

Die-cast trim	Color temperature optional	Mounting bracket
Ultra-thin trim design	Color temperature optional 2700K-5000K	Mounting bracket, with multiple apertures, can be installed into any 2.75 or 3.5inch junction box.

## Size & Dimension &Accessories

Size	Dimension	Accessories
5inch	 <p>Φ5.72" (145.3±2mm) Φ5.53" (142.1±2mm)</p>	 <p>1.59" (40.3±2mm)</p> <p>Mounting bracket</p> 
7inch	 <p>Φ7.5" (190.5±2mm) Φ7.36" (187±2mm)</p>	 <p>1.59" (40.3±2mm)</p> <p>Wire Nuts</p> 
9inch	 <p>Φ8.88" (225.5±2mm) Φ8.72" (221.6±2mm)</p>	 <p>1.59" (40.3±2mm)</p> <p>Screws</p> 

## Recommended Dimmer

LUTRON	INTERTEK
DVSTV-453P	DVSTV-WH